The Power of ONE





64 CH 4K NVR

- > Third-party Network Cameras Supported Onvif
- > Up to 8MP Resolution Recording and Playback
- > Support H.265/H.264 Video Format
- Support 8 SATA up to 48TB Capacity
- Support Max 64,4K IP Cameras
- Max 512 Mbps Incoming Bandwidth
- > HDMI and VGA Output, HDMI up to 4K (3840*2160)



Model	HSN-6464N
Main processor/Operating System	Intel Quad-core Processor / Embedded Linux
Bandwidth	512M/65M 1HDD Playback
Video Standard	H.265/H.264
Monitoring Image Quality	4K / 5MP / 3MP / 1080P / 960P / 720P
Image Motion Detection	multiple detection areas and set 6-level sensitivity
Recording Playback Quality	4*4K / 9* 5MP /16*1080
Region Cover	Every channel can set 4 cover regions(IPC Support)
Recording Mode	Support manual, auto, dynamic detection, alarm trigger record mode
Backup Way	U disk, USB mobile HDD, USB DVD-RW, Network
Recording Storage	Local HDD, network
Video Standard	H.265/H.264
Video Input	64*4K,64*5M,64*2M,36*4K,36*5M,36*2M
Audio I/O	64 /1
Alarm I/O	4/4 1A@24VDC,NO/Relay
Serial Interface	RS-485
Video Output	1ch VGA+1ch HDMI
Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
USB Interface/HDD	1USB 3.0 port, 2 USB 2.0 ports/ 9*SATA+1×eSATA (6TB each)
ONVIF	ONVIF (2.4), IPv4, UPnP (plug and play), NTP , SADP , PPPoE, DHCP ,etc.
Power supply/Consumption	12V/5A, <20W(Without HDD)
Work environment	Temperature:10°C -55°C , Humidity:10%-90%RH , Atm:86kpa-106kp





TVS® is registered trademark of HasH

As a company of innovation, HasH reserves the right to change product specifications without notice. For the latest product specifications, visit online <u>www.tvssecurity.com</u> or contact HasH sales representative.